



(11) **EP 2 199 278 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
23.06.2010 Bulletin 2010/25

(51) Int Cl.:
C07C 269/04 (2006.01)

(21) Application number: **08172275.3**

(22) Date of filing: **19.12.2008**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR**
Designated Extension States:
AL BA MK RS

- **Grego, Sandra**
30030 Salzano (VE) (IT)
- **Rigo, Maurizio**
31022 Preganziol (TV) (IT)
- **Paludetto, Renato**
42015 Correggio (RE) (IT)

(71) Applicant: **DOW GLOBAL TECHNOLOGIES INC.**
Midland, MI 48674 (US)

(74) Representative: **Hull, John Philip**
Beck Greener
Fulwood House
12 Fulwood Place
London WC1V 6HR (GB)

(72) Inventors:

- **Tundo, Pietro**
30174 Mestre (VE) (IT)

(54) **Process for the Production of Aromatic Urethanes**

(57) A continuous process for the production of an aromatic urethane from the reaction of an aromatic amine and an organic carbonate comprising the steps of passing the aromatic amine and the organic carbonate

through a fixed bed reactor containing a zinc carbonate catalyst to produce the aromatic urethane and collecting the aromatic urethane.

Description

[0001] The present invention relates to a continuous process for the preparation of aromatic urethanes from an organic carbonate and an aromatic amine in the presence of a carbamation catalyst.

[0002] Aromatic urethanes are useful intermediates in the preparation of isocyanates. Isocyanates are commonly produced commercially using a reaction between amines and phosgene. However, because of the toxic nature of phosgene, alternative routes are desirable. One way of producing isocyanates which has been discovered is to react an amine with a carbonate to produce a urethane (or carbamate) and then to decompose the urethane thermally to produce the isocyanate.

[0003] The reaction of organic carbonates with amines in the presence of a catalyst is well known and is discussed for example in US3,763,217 and US4,268,684. The catalysts used are typically metal salts, and particularly transition metal salts. A preferred catalyst for producing a urethane for decomposition is zinc acetate, as discussed in US6,034,265. Many other catalysts are disclosed in the prior art as being good catalysts for producing high yields and selectivity, such as Lewis acids, for example antimony trichloride or uranyl nitrate, zinc, tin or cobalt salts.

[0004] EP0065026 discloses the use of zinc naphthenate, zinc acetate, zinc propionate, zinc octoate as suitable catalysts.

[0005] WO99/047493 discloses the use of zinc catalysts such as zinc chloride, zinc acetate, zinc propionate, zinc octoate, zinc benzoate, zinc p-chlorobcnzoate, zinc naphthenate, zinc stearate, zinc itaconate, zinc pivalate, zinc phenolate, zinc acetylacetonate, zinc methoxide, lead catalysts like lead acetate and lead octoate, and tin catalysts like stannous chloride, stannous octoate, and mixtures thereof as suitable catalysts. Zinc or copper carbonate hydroxides are disclosed as possible catalysts in US5,688,988.

[0006] The prior art references typically relate to the use of a tank reactor into which the reactants and catalyst are added. Where the catalyst is heterogeneous, it can be removed by filtration and reused. However, inevitably a proportion of catalyst will be lost by filtration.

[0007] Even though batch reactors can be used in a semi-continuous or continuous manner, they require the catalyst to be added along with the reactants and then filtered out and recycled, which requires significant time and cost. It would be preferable if the reaction could be undertaken in a manner which did not involve recycling of the catalyst by filtration.

[0008] The results of a number of tests carried out by the applicant on various carbamation catalysts indicate that the catalysts are not suitable for use in a continuous fixed bed process as they leach out of the fixed bed, even though they would typically be expected to be insoluble.

[0009] Accordingly, in a first aspect of the present invention, there is provided a continuous process for the production of an aromatic urethane from the reaction of an aromatic amine and an organic carbonate comprising the steps of:

passing the aromatic amine and the organic carbonate through a fixed bed reactor containing a zinc carbonate catalyst to produce the aromatic urethane; and
collecting the aromatic urethane.

[0010] The process according to the present invention advantageously provides a continuous process in which the catalyst does not need to be filtered out from the reaction product. A continuous process is one in which the reactants flow into the reactor and product out of the reactor throughout the whole of the reaction.

[0011] It is preferred that the reaction temperature in the reactor is from 140 to 210°C. It is further preferred that the molar ratio of the organic carbonate and aromatic amine is from 25:1 to 3:1.

[0012] The present invention is suitable for use with any organic carbonate and aromatic amine. However, reactants which are of particular importance are dimethylcarbonate and aniline.

[0013] In a preferred embodiment, the reactor bed additionally comprises non-catalytic particles such as alumina, silica, silica-alumina, activated carbon, titania, zirconia, and diatomaceous earth.

[0014] The term zinc carbonate as used herein is intended to cover any zinc carbonate containing compound of the formula $Zn_a(CO_3)_b(OH)_c(H_2O)_d$ wherein a is from 1 to 4, b and c are from 1 to 7 and d is from 0 to 6.

[0015] The organic carbonate can be any alkyl, aryl or alkyl aryl ester of carbonic acid. The ester group can be an alkyl group with up to 12 carbon atoms, preferably up to 6 carbon atoms, or an aryl group with up to 10 carbon atoms. Suitable organic carbonates include ethylene carbonate, propylene carbonate, styrene carbonate, dimethyl carbonate, diethyl carbonate, dipropyl carbonate, dibutyl carbonate, diisopropyl carbonate, dihexyl carbonate, methyl butyl carbonate, diphenyl carbonate and methyl phenyl carbonate. Dimethyl carbonate (DMC) is particularly preferred.

[0016] The aromatic amine can be a primary or secondary amine, with primary amines being preferred. Preferred amines include aniline, 3,4-dichloroaniline, ortho, meta and para-toluidine, 2, 4-xylidene, 3,4-xylidene, 2,5-xylidene, 3-propyl aniline, 4-isopropyl aniline, methyl aniline, ethyl aniline, isopropyl aniline, butyl aniline, heptyl aniline, 4,4'-diaminodiphenyl methane, 2,4,4'-triamino diphenyl ether, 2,6'-diaminonaphthalene, 4,4'-bismethylene diphenylamine, 4,4'-meth-

ylenedianiline. Particularly preferred is aniline.

[0017] In order to obtain complete conversion of the amine to the urethane, the organic carbonate must be present in at least an equivalent stoichiometric ratio. The organic carbonate is preferably present in an excess in order to minimize the side-reactions such as formation of urea. Preferably, the molar ratio of organic carbonate to amine is from 1:1 to 30:1. It is further preferred that the molar ratio is from 3:1 to 25:1 and more preferably from 6:1 to 22:1. It is particularly preferred that the ratio is from 5:1 to 20:1.

[0018] The temperature of reaction is from 130 to 220°C, and preferably from 150 to 210°C. It is further preferred that the temperature of reaction is from 180 to 210°C. If the temperature is too low, the reactivity reduces. Conversely, if the temperature of reaction is too high, there is an increase in the amount of side products formed.

[0019] The liquid hourly space velocity (LHSV) used in the fixed bed reactor is typically 0.1 to 5.0 hr⁻¹ and more preferably 0.3 to 2.5 hr⁻¹.

The reaction is run using a fixed bed reactor. Any standard fixed bed reactor known to the skilled person would be suitable. Examples of fixed bed reactors are disclosed in "Cocurrent Gas-Liquid Downflow in Packed Beds", Chapter 19, of the Handbook of Fluids in Motion (1983) (R. Gupta) and "Multiphase Catalytic Packed Bed Reactors", Catal. Rev. Sci. Eng. 17 (1978) 71-117 (H. Hofmann). A catalyst is packed in a fixed bed reactor by any suitable method known to the skilled person.

[0020] In addition to the active catalyst, the bed of the reactor can be packed with other filler materials, such as alumina or silica or the like, to reduce the amount of catalyst present in the bed.

[0021] The process should be run under a pressure of 0.5 to 25 MPa, preferably from 0.5 to 10 MPa and more preferably from 1 to 2 MPa.

[0022] The skilled person would be aware of methods of setting up a fixed bed reactor to obtain the required reaction conditions and catalyst levels necessary for high reactivity.

[0023] The invention will now be further described with reference to the following Examples.

EXAMPLES

[0024] A number of tests were run in a batch trial to find catalysts that were suitably reactive. Tests were undertaken in a 235ml stainless steel pressure vessel equipped with a magnetic stirrer and a temperature control system. 100g of reactants (aniline and dimethylcarbonate) were charged into the reactor and the reactivity as measured over time by sampling the mixture during the reaction. Aniline conversion and carbamate selectivity were calculated from the results. The tests were undertaken using various catalysts.

[0025] The reactants used were as follows:

Aniline - Fluka code 10410, purity >99.9%

Dimethylcarbonate - Aldrich code D15292, purity 99, H₂O < 100ppm.

[0026] The catalysts used were:

zinc acetate dihydrate from Poletto S.r.l CAS N. 5970-45-6, MW 219.5;

basic zinc carbonate from Carlo Erba, CAS N. 5260-02-5, MW394.4;

basic lead carbonate from Sigma Aldrich CAS N.1319-46-6, MW775.6;

lead oxide supported on alumina (produced by dissolving a lead salt in water, impregnating the support with the salt until incipient wetness, drying the resulting support for 12 hours at 90°C and calcining at approximately 500°C. The alumina used was Sasol α -alumina No. Z500200 with a particle size of from 0.1 to 0.7 μ m).

[0027] The reaction products were measured using HPLC-UV using nitrobenzene as an internal standard (RP-18 column, eluant water/acetonitrile, gradient from 55/45 to 45/55 in 25 min., flow=1 ml/min.)

[0028] The results of the tests are given in Table 1 below:

Table 1

Example	Catalyst	Mole% catalyst/ mole aniline	Wt % aniline based on DMC	Temp (°C)	Conversion %	Carbamate Selectivity %	Carbamate +Urea selectivity %
1	Zn Acetate	1.6	10	160	91.9	95.1	96.0

EP 2 199 278 A1

(continued)

Example	Catalyst	Mole% catalyst/ mole aniline	Wt % aniline based on DMC	Temp (°C)	Conversion %	Carbamate Selectivity %	Carbamate +Urea selectivity %
2	Zn Carbonate	1.6	10	160	97.0	93.4	96.1
3	Pb Carbonate	1.6	10	160	98.5	98.8	99.0
4	Pb Oxide on Alumina	1.6	10	160	98.6	97.1	97.1

[0029] As can be seen from the results, at the reactant levels and temperatures tested, the lead-containing catalysts show higher conversion and selectivity than those using zinc.

[0030] Zinc carbonate, lead carbonate and lead oxide are insoluble or only slightly soluble in water and are generally insoluble in organic solvents at room temperature.

[0031] Although batch results are of interest, it is important to see whether the heterogeneous catalysts could be used in a continuous flow reactor. In order to test this, a fixed bed reactor was set up using a 4.15ml reactor of 4.6mm internal diameter and 250mm length, with the catalyst being charged in the reactor and packed manually. The tube containing the catalyst was thermostated with a coiled heating band. The reactant solution of aniline and DMC was fed using a Jasco 880 PU HPLC pump. The products, after the reactor, were cooled using a condenser and were collected after a proportional relief valve, set at P = 1.5 MPa. The reaction products were analysed by HPLC-UV as above.

[0032] A solution of aniline (5.0 g, 0.054 moles) and dimethylcarbonate (96.73 g., 1.074 mole), was fed at liquid flow velocity LHSV= 0.72 hr⁻¹ into the continuous flow reactor filled with 2.5 g basic zinc carbonate [ZnCO₃]₂ [Zn(OH)₂]₃ or lead oxide on alumina (4.4g, 11.8% lead).

The reactor was maintained at T=160°C.

[0033] After cooling, the raw reaction product was analysed by HPLC (RP-18 column, eluant water/acetonitrile, gradient from 55/45 to 45/55 in 25 min., flow=1 ml/min.). Samples were taken at various times for each catalyst, as shown in Table 2 below:

Table 2

	Ex 5 Zinc Carbonate		Ex 6 Lead Oxide on Alumina	
Time	5h	32h	5h	20h
Aniline	5.6%	6.4%	10.1%	82.3%
Methyl phenyl carbamate	93.3%	92.2%	87.8%	14.1%
N-methyl aniline	0.6%	0.7%	0.8%	2.4%
N-methylcarbamate	0.0%	0.0%	0.2%	0.0%
N,N dimethylaniline	0.0%	0.0%	0.0%	0.0%
Diphenylurea	0.6%	0.8%	1.1%	1.2%

[0034] From these results it is possible to calculate the following conversion and selectivity values for both catalysts:

- Conversion: 93.3% with respect to the aniline for zinc carbonate after 5 hours and 92.2% after 32 hours.
- Conversion: 89.9% with respect to the aniline for lead oxide after 5 hours and only 17.7% after 20 hours.
- Selectivity with respect to methyl-phenyl carbamate for zinc carbonate: 98.8% after 5 hours and 98.5% after 32 hours.
- Selectivity with respect to methyl-phenyl carbamate for lead oxide: 88.1 % after 5 hours and 79.5% after 20 hours.

[0035] Although both catalysts were thought to be insoluble in the reactants and showed very similar properties when

EP 2 199 278 A1

trialled batchwise, it can be seen clearly that there is a dramatic drop-off in activity seen in the use of the lead oxide catalyst after only 20 hours. Conversely, using the catalyst in the process of the present invention, the conversion and selectivity remain essentially static over a period of 32 hours. In the case of the lead catalyst, the resultant product solution appeared slightly coloured, indicating a leaching of the catalyst.

5 **[0036]** Further tests were undertaken using the zinc carbonate catalyst in relation using different flow rates and reaction temperatures in order to optimise the reaction conditions. The results are shown in Table 3 below

Table 3

Example	DMC/Aniline Ratio	LHSV (hr ⁻¹)	Temp. °C	Conversion %	Carbamate Selectivity %
7	20/1	0.72	160	94.0	98.6
8	20/1	0.72	180	99.0	95.3
9	20/1	0.72	200	99.1	96.5
10	10/1	0.72	160	63.5	91.9
11	10/1	0.72	180	95.2	92.3
12	10/1	0.72	200	97.4	94.6
13	10/1	1.44	180	89.3	93.6
14	10/1	1.44	200	98.1	97.3
15	10/1	1.44	210	96.7	95.6

25 **[0037]** As can be seen from the results, a balance of high temperature and high DMC amount gives the best conversion to carbamate. The reaction conditions of a 20/1 ratio, LHSV of 0.72 hr⁻¹ and temperature of 180°C were tested for 132 hours to test for long term degradation and leaching of the catalyst. The results are shown in Table 4 below.

Table 4

	Zinc Carbonate	
	24h	132h
Time		
Aniline	1.0%	1.0%
Methyl phenyl carbamate	94.1%	95.2%
N-methyl aniline	2.3%	2.2%
N-methylcarbamate	1.6%	1.0%
N,N dimethylaniline	1.0%	0.6%
Diphenylurea	0.0%	0.0%

30 **[0038]** As can be seen, the amount of conversion remained the same at 132 hours as for 24 hours (99%) and the selectivity towards carbamate improved over time. The amount of zinc present in the reaction product was measured using atomic absorption spectroscopy analysis. The resulting product contained only 0.8 mg Zn/l which indicates that the zinc carbonate catalyst is stable in a reaction bed. Surprisingly, therefore, zinc carbonate can be seen to be a catalyst which is not only effective in a batch container, but can also be used in a fixed bed reactor without significant leaching of the catalyst. This catalyst is therefore suitable for use in a long term continuous process.

35 **[0039]** A further test was undertaken using a larger reactor volume of 10.73ml. The amount of catalyst was increased to keep an equivalent amount per unit volume. The flow rate was also increased accordingly. The results showed a comparable conversion rate and carbamate selectivity, suggesting that the continuous process is capable of being scaled up further.

55 **Claims**

1. A continuous process for the production of an aromatic urethane from the reaction of an aromatic amine and an organic carbonate comprising the steps of:

EP 2 199 278 A1

passing the aromatic amine and the organic carbonate through a fixed bed reactor containing a zinc carbonate catalyst to produce the aromatic urethane; and collecting the aromatic urethane.

- 5
2. A continuous process as claimed in Claim 1, wherein the reaction temperature is from 140 to 210°C.
3. A continuous process as claimed in Claim 1 or Claim 2, wherein the molar ratio of the organic carbonate and aromatic amine is from 25:1 to 3:1.
- 10
4. A continuous process as claimed in Claim 1 any one of the preceding claims, wherein the organic carbonate is dimethylcarbonate.
5. A continuous process as claimed in any one of the preceding claims, wherein the aromatic amine is aniline.
- 15
6. A continuous process as claimed in any one of the preceding claims, wherein the liquid space velocity LHSV is from 0.3 to 2.5 hr⁻¹
7. A continuous process as claimed in any one of the preceding claims, wherein the reactor bed additionally comprises non-catalytic particles.
- 20
8. A continuous process as claimed in Claim 7, wherein the additional particles comprise at least one of alumina, silica, silica-alumina, activated carbon, titania, zirconia and diatomaceous earth.
- 25
- 30
- 35
- 40
- 45
- 50
- 55



EUROPEAN SEARCH REPORT

Application Number
EP 08 17 2275

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	WO 2007/015852 A (DOW GLOBAL TECHNOLOGIES INC [US]; MOLZAHN DAVID C [US]) 8 February 2007 (2007-02-08) * page 6, line 28 - line 34; claims * * page 8, line 14 - line 22; examples * -----	1-8	INV. C07C269/04
A,D	US 4 268 684 A (GURGIOLO ARTHUR E) 19 May 1981 (1981-05-19) * claims; examples 10,11,K,L,14-16 * -----	1-8	
A	WO 01/68590 A (ENICHEM SPA [IT]; ENI SPA [IT]; CESTI PIETRO [IT]; BOSETTI ALDO [IT];) 20 September 2001 (2001-09-20) * page 4, line 12 - line 25; claims * -----	1-8	
A	WO 98/55450 A (ICI LTD [GB]) 10 December 1998 (1998-12-10) * page 4, line 1 - line 5; claims * -----	1-8	
A	Z.-H. FU AND Y. ONO: "synthesis of methyl N-phenyl carbamate by methoxycarboxylation of aniline..." JOURNAL OF MOLECULAR CATALYSIS., vol. 91, 1994, pages 399-405, XP002529251 ELSEVIER SEQUOIA, LAUSANNE. * the whole document * -----	1-8	
			TECHNICAL FIELDS SEARCHED (IPC)
			C07C
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
The Hague		26 May 2009	Ginoux, Claude
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03.82 (F04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 08 17 2275

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-05-2009

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2007015852 A	08-02-2007	CA 2615537 A1	08-02-2007
		EP 1943214 A2	16-07-2008
		JP 2009502792 T	29-01-2009
		KR 20080031290 A	08-04-2008
		US 2008227999 A1	18-09-2008

US 4268684 A	19-05-1981	NONE	

WO 0168590 A	20-09-2001	AT 311361 T	15-12-2005
		AU 5468501 A	24-09-2001
		BR 0109464 A	03-06-2003
		CA 2403392 A1	20-09-2001
		CN 1427817 A	02-07-2003
		DE 60115403 D1	05-01-2006
		DE 60115403 T2	27-07-2006
		EP 1268409 A1	02-01-2003
		IT MI20000547 A1	17-09-2001
		JP 2003527367 T	16-09-2003
		MX PA02009139 A	06-09-2004
		US 2003171526 A1	11-09-2003

WO 9855450 A	10-12-1998	AU 8018298 A	21-12-1998
		CA 2289658 A1	10-12-1998
		CN 1258274 A	28-06-2000
		HU 0003114 A2	28-02-2001
		JP 2002512626 T	23-04-2002
		ZA 9804538 A	07-12-1998

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 3763217 A [0003]
- US 4268684 A [0003]
- US 6034265 A [0003]
- EP 0065026 A [0004]
- WO 99047493 A [0005]
- US 5688988 A [0005]

Non-patent literature cited in the description

- Cocurrent Gas-Liquid Downflow in Packed Beds. **R. Gupta**. Handbook of Fluids in Motion. 1983 [0019]
- **H. Hofmann**. Multiphase Catalytic Packed Bed Reactors. *Catal. Rev. Sci. Eng.*, 1978, vol. 17, 71-117 [0019]